
1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name ACETYLENE
Synonyms DISSOLVED ACETYLENE

1.2 Uses and uses advised against

Uses INDUSTRIAL APPLICATIONS

1.3 Details of the supplier of the product

Supplier name POWER 10 GASES PTY LIMITED
Address 9/10 Pioneer Ave, Thornleigh, NSW, 2120, AUSTRALIA
Telephone 1300 669 868
Email enquiries@power10gases.com.au
Website <http://www.power10gases.com.au/>

1.4 Emergency telephone numbers

Emergency 1300 669 868
Poisons Information Centre 13 11 26

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Flammable Gases: Category 1
Gases Under Pressure: Dissolved gas
Explosive with or without contact with air

Health Hazards

Not classified as a Health Hazard

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms**Hazard statements**

AUH006 Explosive with or without contact with air
H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.

Prevention statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

PRODUCT NAME ACETYLENE**Response statements**

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.

Storage statements

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statements

None allocated.

2.3 Other hazards

Asphyxiant. Effects are proportional to oxygen displacement.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (v/v)
ACETYLENE	74-86-2	200-816-9	>98%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye Adverse effects not expected from this product.
Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.
Skin Adverse effects not expected from this product.
Ingestion Ingestion is not considered a potential route of exposure.
First aid facilities None allocated.

4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.

4.3 Immediate medical attention and special treatment needed

Treat for asphyxia.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve. If the gas source cannot be isolated, do not extinguish the flame, since re-ignition and explosion could occur. Await arrival of emergency services or manufacturer's advisor. Drench and cool cylinders with water spray from protected area at a safe distance. If it is absolutely necessary to extinguish the flame, use only a dry chemical powder extinguisher. Do not move cylinders for at least 24 hours. Avoid shock and bumps to cylinders.

5.2 Special hazards arising from the substance or mixture

Extremely flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. This material is capable of forming explosive mixtures in air.

5.4 Hazchem code

2SE
2 Fine Water Spray.
S Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Dilute spill and run-off.
E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Eliminate all sources of ignition. Consider the risk of potentially explosive atmospheres.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement. Never open an acetylene cylinder valve without the regulator attached. Gas regulator of suitable pressure and flow rating fitted to cylinder and manifold with low pressure gas distribution equipment which controls fuel gas mixture and flame. The regulator and other equipment must be compatible with the product and suited for the particular use. Never "sniff" acetylene as it may ignite spontaneously. Instead, carefully inspect the outlet and if there are any signs of dirt, blow it out with a jet of clean compressed air or nitrogen.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible substances and sources of ignition. Cylinders should be stored: upright, prevented from falling, in a secure area; below 65°C, in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits. Post "No Smoking or Open Flames" signs in the storage areas. Refer to applicable legislation on flammable storage quantity restrictions. Never transfer acetylene to another cylinder or other container.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Acetylene	SWA [AUS]	Asphyxiant			

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (e.g. tanks) should be adequately ventilated or gas tested. Flammable/explosive vapours may accumulate in poorly ventilated areas.

PRODUCT NAME ACETYLENE

PPE

Eye / Face	Wear safety glasses.
Hands	Wear leather or cotton gloves.
Body	Wear coveralls and safety boots.
Respiratory	If using product in a confined area, wear an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	COLOURLESS GAS
Odour	GARLIC-LIKE ODOUR
Flammability	EXTREMELY FLAMMABLE
Flash point	< 23°C
Boiling point	-84°C
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	0.906 (Air = 1)
Relative density	NOT APPLICABLE
Solubility (water)	SOLUBLE
Vapour pressure	4700 kPa @ 25°C
Upper explosion limit	80 % to 85 %
Lower explosion limit	2.5 %
Partition coefficient	NOT AVAILABLE
Autoignition temperature	305°C
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

9.2 Other information

% Volatiles	100 %
Critical pressure	6,242 kPa
Critical temperature	36.3°C (dissolved in acetone and porous medium)
Cylinder pressure (when full)	1550 kPa @ 15°C

10. STABILITY AND REACTIVITY

10.1 Reactivity

Forms explosive acetylides with copper, silver and mercury. Do not use alloys containing more than 65% copper.

10.2 Chemical stability

Stable under recommended conditions of storage. However, sensitive to heat or shock and may become explosive.

10.3 Possibility of hazardous reactions

Polymerises with evolution of heat. Avoid contact with curing agents, accelerators, and/or initiators.

10.4 Conditions to avoid

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), copper, copper alloys (>70% copper), silver and mercury to form explosive acetylides. May decompose violently at high temperatures and/or pressures or in the presence of a catalyst. Hazardous by-products may be produced when this gas/gas mixture is used in welding, cutting and associated processes.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin	Not classified as a skin irritant.
Eye	Not classified as an eye irritant.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Not classified as a reproductive toxin.
STOT - single exposure	Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness, drowsiness, weakness, fatigue, breathing difficulties and unconsciousness.
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure.
Aspiration	Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No ecological damage is expected to be caused by this product.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate.

12.4 Mobility in soil

Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5 Other adverse effects

No known effects from this product.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



PRODUCT NAME ACETYLENE

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1001	1001	1001
14.2 Proper Shipping Name	ACETYLENE, DISSOLVED	ACETYLENE, DISSOLVED	ACETYLENE, DISSOLVED
14.3 Transport hazard class	2.1	2.1	2.1
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code 2SE

GTEPG 2A1

EmS F-D, S-U

Other information

Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport. Special transport precautions: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

Ensure there is adequate ventilation.

Ensure that containers are firmly secured.

Ensure cylinder valve is closed and not leaking.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Ensure valve protection device (where provided) is correctly fitted.

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

Inventory listings **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**
All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION**Additional information**

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders. When using this gas/gas mixture for welding, cutting and associated processes, additional hazards may be generated by the process such as radiation, noise and fume. Risk assessments should be made for each activity to identify and quantify the individual hazards involved. Please refer to the relevant Safety Data Sheets for the welding consumables being used or, if available, the materials being welded.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PRODUCT NAME ACETYLENE**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]